

PORTABLE MESSAGE WAITING INDICATOR

Inventor: Ian Andrew Bell

5

BACKGROUND

This invention relates to the field of communications. More particularly, an apparatus and methods are provided for indicating the receipt of a communication.

Various devices and methods have been introduced for the purpose of
10 notifying a person that a telephonic message has been received for him or her. Answering machines, for example, typically indicate the receipt of a message by flashing a light and/or displaying the number of messages.

The advent of network-based voice-mail service has made it somewhat more difficult to provide an easy, simple and fast way to notify a person that he or
15 she has received a message. With network-based voice-mail service, the person's messages are stored in a remote location operated by the provider of the voice-mail service (e.g., the person's local telephone company). Unlike with an answering machine, with network-based voice-mail service there are no means of quickly (e.g., visually) alerting a person to the receipt of a message. Typically the
20 person must take his or her telephone off-hook to test for a stutter-tone that indicates receipt of a message.

This requires proactive effort by a person, in contrast to simply looking at a visual indicator, is not as easy, and may not be possible at all times. In particular, because the person must physically access a telephone he or she cannot
25 test for stutter-tone when traveling or otherwise away from the telephone.

Another problem with many existing systems for indicating message-waiting status is that they do not function if a person's telephone line is in use. A

person cannot test his telephone line for stutter-tone while using it to talk to someone, access the Internet, etc.

Further, stutter-tone is line-specific in that from one telephone a person can only check for messages waiting in a voice-mail system for that telephone
5 line. While at work, a person cannot check for messages received by her residential telephone service, and vice versa.

Many message waiting indication systems are thus dependent upon or tied to calls to or from a particular telephone line, place (e.g., residence, office) and/or device (e.g., a specific telephone). As a result, indicating receipt of a message for
10 a user of a central (e.g., network-based) voice-mail service generally requires the user to adopt new behavior and/or pay extra money for specialized notification services or systems.

Even the user of pager notifications to alert someone that he or she has received a voice-mail message has disadvantages. For example, a paging system
15 may require manual deactivation, in that the person may be required to take some action (e.g., save or delete the message) in order to avoid being paged multiple times for a single message. Further, in order for a pager to inform a person of messages on more than one telephone line or at multiple locations, the pager or pager service must be configured separately for each line or location.

20 Therefore, what is needed is an apparatus and method of notifying someone of the receipt of a voice-mail message for him or her. The apparatus should be portable, easy to use and should not be limited to use at just one location or with just one telephone or telephone line. The apparatus should be configurable in as few steps (e.g., one) as possible, and it may be desirable for the
25 apparatus to be automatically deactivated when a message is retrieved.

SUMMARY

In one embodiment of the invention an apparatus and methods are provided for notifying a person that he or she has received a communication, regardless of whether the person is using his or her telephone line. In this
5 embodiment the device is designed for simple operation to readily indicate a message-waiting status, and provides independence from any particular place or telephone line. In addition, multiple devices may be employed to indicate message-waiting status for one line or one device may be used to indicate message-waiting status for multiple lines.

10 In a present embodiment a user employs a message waiting indication device (MWID) to determine when he or she has received a communication (e.g., a telephone call, an electronic mail message, a facsimile). In this embodiment a MWID includes a power source (e.g., a battery), a receiver for receiving notification of a communication and an indicator such as an LED (Light Emitting
15 Diode) or audible alarm. When a communication is received for the user, a first signal is sent to the MWID and the indicator is activated. Receipt of a second signal may turn the indicator off. The small size, light weight, unobtrusive nature and low power requirements of the device make it portable and easy to keep with a person when a larger device (e.g., a telephone) would be awkward.

20 In another embodiment of the invention a MWID may include means (e.g., a button or pad) for turning the indicator off.

In one method of using a MWID, a user registers the device with his or her voice-mail service or other organization charged with providing him or her with notification of communications. In this method a MWID is assigned a unique
25 code (e.g., serial number), which may be stamped or printed on the device. The user may register more than one device for a specific telephone line (e.g., home or office), electronic mail account, purpose (e.g., indicate receipt of a telephone call,

electronic mail message, facsimile) or one device for multiple telephone lines, purposes, etc. A user's message waiting indication service may be configured to indicate receipt of a communication from all sources (e.g., all telephone calls), a specific source (e.g., an electronic mail message from a specific sender) or from
5 multiple sources (e.g., all calls received from a specific area code).

When a user receives a communication meeting the criteria for which a MWID is configured, a signal is sent to the MWID and its indicator is activated. The user may deactivate the indicator manually if the MWID is so designed, and/or a second signal may be sent to the MWID to deactivate it when the user
10 accesses retrieves the communication. In one embodiment of the invention an "empty" or "true" signal is sent to a MWID to activate its indicator, while a "not empty" or "false" signal is sent to deactivate it.

DESCRIPTION OF THE FIGURES

15 FIG. 1 is a block diagram depicting a system for indicating to a user the receipt of a communication in accordance with an embodiment of the present invention.

FIG. 2 is a block diagram illustrating a message-waiting indicator in accordance with an embodiment of the invention.

20 FIG. 3 is a flowchart illustrating one method of employing the message-waiting indicator of FIG. 2 in accordance with an embodiment of the invention.

DETAILED DESCRIPTION

The following description is presented to enable any person skilled in the
25 art to make and use the invention, and is provided in the context of particular applications of the invention and their requirements. Various modifications to the disclosed embodiments will be readily apparent to those skilled in the art and the

general principles defined herein may be applied to other embodiments and applications without departing from the spirit and scope of the present invention.

Thus, the present invention is not intended to be limited to the embodiments shown, but is to be accorded the widest scope consistent with the principles and
5 features disclosed herein.

The program environment in which a present embodiment of the invention is executed may incorporate a general-purpose computer or a special purpose device such as a hand-held computer. Details of such devices (e.g., processor, memory, data storage, display) are omitted for the sake of clarity.

10 It should also be understood that the techniques of the present invention might be implemented using a variety of technologies. For example, methods described herein may be implemented in software executing on a computer system, or implemented in hardware utilizing either a combination of
15 microprocessors or other specially designed application specific integrated circuits, programmable logic devices, or various combinations thereof. In particular, a method described herein may be implemented by a series of computer-executable instructions residing on a storage medium such as a carrier wave, disk drive, or computer-readable medium. Exemplary forms of carrier waves may take the form of electrical, electromagnetic or optical signals
20 conveying digital data streams along a local network or a publicly accessible network such as the Internet.

In one embodiment of the invention a message-indicating device or message waiting indication device (MWID) is provided to indicate to a user that he or she has received a communication. The communication may be a voice-
25 mail message, an electronic mail message, or any other type of communication. In this embodiment the MWID is small, lightweight, unobtrusive and simple to use. It includes an indicator that, when activated (e.g., by a wireless paging

signal), informs the user of the communication. The indicator may provide a visual and/or an audible alert, and may be an LED (Light Emitting Diode) or other suitable element.

5 The MWID also includes a power source (e.g., a battery), which may or may not be replaceable. Therefore, a MWID may be disposable. A MWID may include a user-operable switch, button or sensor to deactivate the indicator. The indicator may also, however, be deactivated in response to receipt of a second signal that is different from the signal that activates the indicator. Thus, after the user accesses or acknowledges receipt of the communication, the second signal
10 may be sent to deactivate the indicator.

FIG. 1 depicts one system in which a MWID may be employed to notify a user of a voice-mail message, according to one embodiment of the invention. In FIG. 1, a telephone call is initiated to a user from one of communication devices 102a, 102b. Telephone 102a may be wired or wireless telephone, and computer
15 102b may be a desktop, laptop, hand-held or other type of computer. Although the system of FIG. 1 is described in the context of a voice-mail message, in other embodiments of the invention different types of communications (e.g., electronic mail, facsimile) and communication devices may be employed.

The telephone call is routed through switch (e.g., a telephone company's
20 central office, an Internet service provider) or gateway 104 to telephone 112a or computer 112b, which are associated with the user. In this example, however, the user is unavailable at the time of the call. He or she may already be using one of the devices for another purpose, may be away or may be otherwise occupied.

Therefore, the call is forwarded or rerouted to voice-mail server 106,
25 which may be part of a central or network voice-mail system. At voice-mail server 106 the caller leaves a voice-mail message, which may be recorded in his or her own voice or may be computer generated (e.g., through computer 102b).

Voice-mail server 106, or a system comprising server 106, then issues a first signal (e.g., a paging signal) to the user's MWID 114. The signal may be sent through transmitter 108 or whatever other signal generation and distribution system is available or appropriate (e.g., wired, satellite). Upon receipt of the signal, the MWID activates an indicator to alert the user that a communication has been received.

In this embodiment of the invention the first signal may be an "empty" paging signal. In other words it may comprise a header but no body. Alternatively, it may include a very short body (e.g., a single character or digit). When the user retrieves, accesses or otherwise acknowledges the communication (e.g., by playing back the voice-mail message), a second signal may be sent to MWID 114. When the second signal is received, the indicator is deactivated. Illustratively, such a second signal is different from the first signal that activated the MWID indicator. Thus, if the first signal is an empty page, the second signal may be a page with a short body (e.g., one character or digit).

In one embodiment of the invention MWID 114 may include a user-operable switch to deactivate the indicator.

FIG. 2 is a block diagram of a MWID according to a present embodiment of the invention. MWID 200 of FIG. 2 includes power source 202, receiver 204, indicator 206 and, optionally, switch 208. MWID 200 exhibits the shape of a rounded square, but the configuration of a message waiting indication device is not limited to that of MWID 200. In other embodiments of the invention a MWID may assume many different shapes and configurations. In particular, a MWID may be shaped to attach to, appear similar to, or include another object (e.g., a key, a writing implement, a fob).

Power source 202 may be any of various types (e.g., nickel-metal hydride, lithium-ion), sizes and specifications. It is estimated that approximately three

volts is sufficient to operate a MWID configured as shown in FIG. 2. As a battery, power source 202 may or may not be replaceable. Also, although not shown in FIG. 2, MWID 200 may include a socket or slot to hold a spare battery. In one alternative embodiment of the invention power source 202 may be a photovoltaic power cell capable of converting light or solar power to electricity to operate the MWID.

Receiver 204 is configured to receive radio (e.g., wireless) signals, as described in conjunction with FIG. 1, to activate and deactivate indicator 206.

Indicator 206 may provide a visual, audible and/or vibratory alert when receiver 204 receives an appropriate signal. Thus, indicator 206 may comprise an LED, LCD (Liquid Crystal Diode), speaker or other such element. Indicator 206 may be capable of one or more alert types. For example, a user may configure a MWID (e.g., through a registration process as described below) so that its indicator flashes with one interval or pattern in one situation and a different interval or pattern in a second situation. Thus, the number of consecutive flashes may indicate a number of communications, a communication priority, a telephone line on which a voice-mail message was left, a type of communication (e.g., voice-mail, electronic mail), etc.

In one alternative embodiment of the invention, multiple indicators may be included on a MWID to indicate receipt of different types of communications, receipt of a message at a different location (e.g., residence, office, mobile telephone), different priorities of messages, etc.

Switch 208, if included in a MWID, allows a user to manually deactivate indicator 206 after it is activated. In one embodiment of the invention indicator 206 may incorporate switch 208. Thus, a user may wish to deactivate the indicator after it alerts him or her to a communication, without having to first access the communication. As described above, a specific signal may be sent to a

user's MWID to deactivate its indicator after the user accesses his waiting communication(s).

In an embodiment of the invention in which the device adopts the rounded square shape of FIG. 2, the dimensions of MWID 200 may be approximately .5"
5 long by .5" wide by .3" thick. Further, the MWID may include a hole or other means of attaching to a key chain or other organizer. Yet further, the MWID may have a serial number or other identification code printed on it.

amended claim 1

The portable nature of the device makes it very easy to use without being obtrusive, and it can even be disposable. A MWID may include a hole, hook,
10 adhesive or other means of being attached to something. Thus, MWIDs could be attached to key chains, computer systems, telephone equipment, car dashboards, and other locations from which a user can be easily and quickly notified that a communication is awaiting him or her. Illustratively, adhesive (e.g., regular or double-backed tape, non-permanent glue) may be placed on the back of the
15 MWID to allow for easy and/or removable attachment to a wall, telephone, other device, furniture, etc.

FIG. 3 demonstrates one method of notifying a user of a communication with a message waiting indication device such as MWID 200 of FIG. 2. Other methods of employing a MWID may be derived from FIG. 3 and the
20 accompanying discussion.

In state 300 of FIG. 3, a user registers a MWID. The MWID may, for example, be provided by the organization providing voice-mail service or an Internet service to the user. The user may, upon receipt of the MWID, access a web site of the organization to register and configure the MWID or may do so
25 telephonically.

not configure on server

Illustratively, registration of a MWID may entail associating the MWID (e.g., by serial number) with the user and indicating when it should be activated.

Thus, the user may indicate that he or she wishes to register the device for use with a certain telephone number (e.g., for voice-mail messages left for the user at that number) or multiple telephone numbers. Thus, one MWID may be employed to indicate receipt of a voice-mail message at any of several telephone numbers.

- 5 Conversely, multiple MWIDs may be associated with a single telephone number, in which case each may be configured differently or they may be configured identically.

Although multiple MWID are used, but, deactivation to all these MWID is not disclosed.

- 10 The user may specify that he or she is to be alerted (i.e., the MWID activated) for every voice-mail message left for him or her, for every message from a particular person, telephone number or collection of telephone numbers.

The user may specify that he or she is only to be alerted for certain types (e.g., voice-mail messages, electronic mail messages), lengths or priorities of messages, etc. In summary, each MWID may be registered and configured separately to alert a user to different communication statuses. Users may also be able to de-register a MWID.

Also, not all MWID are activated at the same time for all same message.

If the user's MWID is capable of multiple indication patterns (e.g., different LED flashing intervals or sequences), the user may also specify which pattern is to be used for different types of communications, different communication priorities, different numbers of communications and other criteria.

- 20 In state 302 a communication is sent to the user. The communication may be a voice-mail message, an electronic mail message, a facsimile, a page, etc.

- In state 304, the organization tasked with managing notifications to the user via his or her MWID recognizes that the communication is waiting. Illustratively, this organization may also operate the system on which the communication was received, in which case states 302 and 304 may be performed substantially simultaneously. Otherwise, the organization is notified of the communication or checks the user's voice-mail box or electronic mail box or
- 25

other communication repository on a periodic basis to determine if any communications await the user's attention.

In state 306, the organization initiates a first signal to the user's MWID. Illustratively, this may simply comprise an empty paging signal or other simple
5 wireless signal.

In response to the first signal, in state 308 an indicator on or in the user's MWID alerts the user that he or she has one or more communications waiting. The manner in which the indicator flashes, beeps, vibrates or otherwise signals the user may indicate the type, source, size, number, priority or other characteristic of
10 the communication.

If, in state 310, the user retrieves his or her communication(s), then in state 312 a second signal, possibly different from the first signal, is sent to the MWID. In response to this, in state 314 the MWID indicator is deactivated.

Otherwise, in one embodiment of the invention, in state 316 the user may
15 manually deactivate the MWID indicator. This may be done, for example, by manipulating a sensor, switch, button or other portion of the MWID provided for this purpose. As with the second signal, manipulation of such a switch will cause the indicator to be deactivated in state 314.

20 The foregoing descriptions of embodiments of the invention have been presented for purposes of illustration and description only. They are not intended to be exhaustive or to limit the invention to the forms disclosed. Accordingly, the above disclosure is not intended to limit the invention; the scope of the invention is defined by the appended claims.

25 For example, the wireless signals used to activate and deactivate a message waiting indication device (MWID) in an embodiment of the invention may be of various types or within various frequency bands. In one

implementation radio paging may be employed, in which case the receiver included in the MWID is a radio-paging receiver. In this implementation, one radio paging signal or ping could be used to activate the MWID indicator, while a second signal, or two successive pings, could deactivate the indicator. This

5 implementation may be particularly well suited for an environment in which an inexpensive device is desired that can operate on the power provided by a small battery. Further, signaling such a device requires little network utilization, thus keeping the cost of each signaling event low.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219